



TC 1550 HS DP1

Dynamic Punching Unit



Dynamic Punching unit for 2-up production

- ✓ *Two punching wheels for 2-up production*
- ✓ *2, 3 or 4 holes pattern per wheel*
- ✓ *Speed up to 150 m/min for 12" forms*
- ✓ *Read & Punch On The Fly*
- ✓ *On board tensioner/detensioner (optional)*

The TC 1550 HS DP1, dynamic punching unit is the perfect solution to produce reliable documents with accurate punching patterns for easy paper handling and storage.

The TC 1550 HS DP1 has 1 punching device, with two independent punching wheel for 2-up applications. Wheels can be equipped with 2, 3 or 4 punching patterns to fit different applications.

The TC 1550 HS DP1 performs punching patterns through a OMR, Barcode or Datamatrix reader to ensure on-the-fly application jobs

and maximum flexibility. A vacuum system is integrated into the unit to clean the web and prevent that paper waste is transferred to the following processes.

Tecnau solutions increase productivity, cut labor and paper costs, and even make new applications possible. Global service and around-the-clock support help ensure our reputation as the industry's reliability leader. Innovative products combined with award winning support and service make Tecnau the essential partner for your print operation.




TC 1550 HS DP1

Dynamic Punching Unit

The Dynamic Punching TC 1550 HS DP1 has been developed to work with tight or slack paper webs, in line with Laser Printers, high speed inkjet Digital Printing Systems and finishing equipments. The main feature for this product are:

- ✓ One punching device, with two independent punching wheels for 2-up applications.
- ✓ The punch device is activated by 1D or 2D code reading with start/stop motion performing the punch pattern.
- ✓ Different hole diameters available on the same punching wheel (1/4" - 3/8" DIA).
- ✓ Manual adjustment of the vertical file holes line at the paper web position.
- ✓ Programmable punching position.
- ✓ Punching position microprocessor controlled by OMR or Bar Code or D-Matrix readers.
- ✓ "Read & Punch On The Fly" software for automatic detect and perform the applications, switching from one application to another within one sheet module.
- ✓ Up to 89 different applications can be stored.
- ✓ Automatic synchronization after blank paper.
- ✓ Display and keyboard for programming, information and services.
- ✓ Parallel and serial interface.

Configuration Example



Technical Specifications


Performance / Media

Speed Max	500 ft/min	150 m/min
Paper weight	28# - 177# text	40 - 250 gsm
Web width	4" - 22" <i>up to 23" on request</i>	102 - 560 mm <i>up to 584 mm on request</i>
Web process width	4" - 20.5" <i>up to 22" as special</i>	102 - 521 mm <i>560 mm as special</i>
Capabilities	1 Dynamic hole punching unit	
Form Length	4" - 32" <i>up to 88" special</i>	89 - 812 mm <i>up to 2235 special</i>
Punching App.	2-, 3-, 4-holes	2-, 3-, 4-holes <i>Other applications are available on request</i>

Electrical

Power	EU: 3Ph+PE, 400Vac, 50Hz, 11A US: 3Ph+PE, 480Vac, 60Hz, 9A	
Air	20 litres/min @ 4 bar pressure	

Application Examples



22042024

©2024 Tecna. All rights reserved. The Tecna name and logo are trademarks of Tecna. Tecna reserves the right to make any technical amendments without prior notification.



TECNAU

w w w . t e c n a u . c o m

Europe	Italy	+39 0125 631678	info.it@tecna.com
	Sweden	+46 372 256 00	info.se@tecna.com
Americas	USA	+1 978 608 0500	info.us@tecna.com
Asia Pacific	China	+86 159 00710147	info.cn@tecna.com
	Singapore	+65 6793 9478	info.sg@tecna.com